



VIDEO RECEIVER

MODEL BA2006

SPECIFICATIONS:

- **Frequency:** Single frequency in the range of 1000 to 2500 MHz
- **Sensitivity:** -87 dBm
- **RF Input impedance:** 50 Ohm
- **Demphasis:** per CCIR405
- **Image Rejection:** 70dB min
- **Video Output level:** 1 V_{ptp} for a deviation of ± 5 MHz
- **Video Output impedance:** 75 Ohm
- **RF Connector:** SMA type
- **Video Connector:** BNC
- **Dimensions:** 137x54x20 mm (excluding connectors)
- **Weight:** 365 gr
- **Supply Voltage:** 12 ± 2 V
- **Current consumption:** 240 mA



OPTIONS:

BA2006B VIDEO/AUDIO RECEIVER:

- **Audio Frequency:** 50 Hz - 5 KHz
- **Output:** 1 V_{ptp} into 1 kOhm load.pins
-

BA2006X CRYSTAL CONTROLLED FREQUENCY AND

BA2006BX AUDIO AND CRYSTAL CONTROLLED FREQUENCY:

- **Stability:** ± 2.5 ppm over the temperature range.

BA2006S SYNTHESIZED FREQUENCY

BA2006BS AUDIO AND SYNTHESIZED FREQUENCY